

WHAT'S IN THE BOX

Please read each step before you attempt to set up. Save these instructions for future reference.


- 1- 10' x 10' Cabana™ Frame Fully Assembled
- 1- Cabana™ Polyester Top
- 1 - Cover Bag
- 4 - Piece Stake Set

HOW TO SET UP


Note: First Time Attachment Is Required

Top and frame are shipped unattached to avoid damage. A first time set up requires that top be bolted on to the frame. This first-time set up takes a few minutes. Once top is permanently attached to frame, set up and take down are easily accomplished within seconds.


1. Place your E-Z UP® frame in the center of area to be shaded. With partner on opposite side, grasp outer legs, lift off the ground, and step backwards - stopping at full arm's length - approximately 3/4 it's total size.



* 2. Gently unfold the fabric top and place it over the open frame.



* 3. Attach the Cabana™ top to the E-Z UP® frame by placing the four corner pockets over end of all four top extensions.




* 4. To secure the top to the frame, line up the grommet holes on the valance with the four existing pre-drilled holes on the frame.


* 5. With screwdriver provided, put screw through grommet hole into the pre-drilled hole and secure on all four top frame top extension.




6. Pull out top extension rods until the snap button engages the hole.



7. Grasp the bottom of the diamond (shown), on opposite sides. Lift up and step backwards until shelter is fully opened. Be careful not to pinch fingers.




8. Engage the auto slider at each corner by pushing up with one hand while holding down the top of the leg with the other hand. The snap button will engage the hole. Then pull down the hem of the top. Repeat at all four corners.




9. Stand under shelter and locate center hub. Place hand beneath center hub and push up, extending top frame inner peak beams. Keep hand in place and push up until at least two inner peak beams lock.

Warning: Do not let go of center hub until at least two peak beam assemblies lock. Extend remaining top frame inner peak beam so all four tubes are snapped into place.




10. Lift two adjacent outer legs up 1" and slide out the inner legs until the snap button locks. Repeat on the opposite legs - make sure to do two legs at a time.



***Note:** Once top is permanently attached only perform steps 1 and 6-10 to set up.


How To TAKE DOWN

1. With partner, slightly lift two adjacent outer legs up 1", depress the snap button, and telescope the inner legs up into the outer legs. Repeat on the opposite legs - making sure to do two legs at a time.




2. Stand under shelter and locate center hub. Place hand beneath center hub and hold while releasing top frame inner peak beams by pushing snap buttons on all four top frame inner peak beams to disengage.


Warning: After all four peak beam assembly snap buttons are released, gently lower center hub. Center hub should drop down in an inverted position and rest near the ground.



3. Release top extension rods at each corner while depressing snap button with other hand.



4. Release auto slider at each corner by first lifting hem of top. With one hand push up on truss near slider, depress snap button. **Note:** It is much easier to depress the snap button when the shelter weight has been removed from the snap button.



5. Grasp the top diamond on opposite sides by "close" sticker. Lift the shelter up slightly and shake it while stepping towards your partner until the unit is 3/4 closed. With each partner grasping two outer legs, push shelter together to fully close it. **Be careful not to pinch fingers!** Store E-Z UP® in cover bag.

